

Email: sales@scilabexport.com

Phone: +91-7082934803

# **Product Name:**

**Product Code:** 

Francis Turbine Trainer

SLE/MCE/46





Email: sales@scilabexport.com

Phone: +91-7082934803

## **Description:**

#### **Description:**

- A centrifugal pump and a flow control valve for adjusting the inlet pressure.
- The transparent operating area of the turbine enables an optimal view of water flow, rotor and guide vanes during operation.
- By adjusting the guide vanes the angle of attack, the cross-section and thus the output of the turbine are changed. An asynchronous machine is used as a generator for loading the turbine.
- The generator is equipped with a pendulum bearing and with a force sensor to determine the torque.
- A pump with variable speed via frequency converter provides for an energy efficient operation.
- The measured values are displayed digitally and can be processed further on a PC.
- The speed of the turbine is recorded by means of an inductive, non-contact position sensor at the generator shaft.
- The pressures at the inlet and outlet of the turbine, the temperature and the flow rate are recorded by sensors.

#### Specification:

• Hydraulic power: 2,1kW at 1500min-1

Mechanical power: approx. 1,4kW at 1500min-1

• **Rotor**, **D**: 165mm

• 8 blades, 8 guide vanes

Angle of attack adjustable: 0...23°

· Centrifugal pump, multistage.

### Variable speed:

• Pump head: 42m

• Tank: 550L

Power consumption: 5,5kWMax. Flow rate: 900L/min

Asynchronous machine as generator

• Output: 2,2kW at 1440min-1

#### Measuring ranges:

• Temperature: 0...100°C

Pressure (inlet): ±1bar (turbine)
Pressure (outlet): 0...6bar (turbine)

• Flow rate: 0...1000L/min

Torque: 0...20NmSpeed: 0...3000min-1

#### Power supply:

• 0...2200W (generator)

• 400V, 50Hz, 3 phases

• 400V, 60Hz, 3 phases, 230V, 60Hz, 3 phases

• **Dimension**: 2350x1050x2050mm

• Weight: approx. 580kg

Contact Scie best educati in ambala, la



 ${\bf Email: sales@scilabexport.com}$ 

Phone: +91-7082934803