



Email : sales@scilabexport.com

Phone: +91-7082934803

Product Name :

Solar Direct Drive Refri 46.5L

Product Code :

SLE/CCE/08



Website: <https://scilabexport.com>, **Email:** sales@scilabexport.com

1226/1-5, Bengali Mohalla, Science Market | 133001, Haryana



Email : sales@scilabexport.com

Phone: +91-7082934803

Description :

Solar Direct Drive Refri 46.5L (Product Code: SLE/CCE/08) is a mid-size solar direct drive refrigerator used to store vaccines at off-grid health facilities that need more space than a compact unit but less than a store-size appliance. It has 46.5 litres of net vaccine storage, uses R600a refrigerant and is listed with solar panels of Indian origin. It is supplied by **Jain Scientific Equipments Pvt Ltd (ScienceLab)**, Ambala, India, for scientific equipment bulk supply and programme orders.

Specifications

Parameter	Detail
Type	Complete stand-alone SDD refrigerator with all necessary components and fittings (plug and play)
Net vaccine storage volume	46.5 litres
Refrigerant	R600a
Ambient operating temperature	Min. +10°C, max. +43°C
Freeze protection	Grade A
Solar power system	Matched to the refrigerator's power consumption, climate, ambient temperatures and a solar radiation reference of 3.5 kWh/m ² per 24 hours
Solar panel origin	India
Manuals	User, installation and technician's manuals in English
Product code	SLE/CCE/08
Supplied by	Jain Scientific Equipments Pvt Ltd (ScienceLab), Ambala, India

What Is the Solar Direct Drive Refri 46.5L Used For?

This refrigerator keeps the routine vaccine stock of a dispensary, sub-district clinic or mission hospital cold where grid power cannot be trusted. At 46.5 litres, it leaves space for incoming deliveries to be sorted by antigen and expiry without overfilling, which helps cold air reach every vial. Because the compressor is driven by the solar array, the facility does not need fuel or a generator to keep the cold chain running.

The panels listed for this model are of Indian origin, a detail some buyers record for procurement files. Like other hot-climate SDD units, it is specified for ambient temperatures of +10°C to +43°C, so place it in a room that stays within that band and keep the solar cabling protected from damage.

What to Specify When Ordering

- Quantity
- Room temperature
- Any particular requirements
- Local agent

Website: <https://scilabexport.com>, **Email:** sales@scilabexport.com

1226/1-5, Bengali Mohalla, Science Market | 133001, Har yana



Email : sales@scilabexport.com

Phone: +91-7082934803