Email : sales@scilabexport.com
Phone: +91-7082934803

Product Name :

Mains Ref 128L

Product Code :

SLE/CCE/015



Science Lab
Email : sales@scilabexport.com
Phone: +91-7082934803

Description :

Mains Ref 128L (Product Code: SLE/CCE/015) is a mains-powered vaccine refrigerator used to store large vaccine stocks at grid-connected health centres, hospitals and vaccine stores. It provides 128 litres of net vaccine storage with R134a refrigerant and Grade A freeze protection, and is listed for either 220-240V 50/60Hz or 100-127V 50/60Hz supplies. It is manufactured by **Jain Scientific Equipments Pvt Ltd (ScienceLab)**, Ambala, India, a laboratory equipment supplier in India that also handles export orders.

Specifications

Parameter	Detail
Net vaccine storage volume	128 litres
Vaccine storage volume category	?120 L
Refrigerant	R134a
Ambient operating temperature	Min. +5°C, max. +43°C
Freeze protection	Grade A
Power requirement	220-240V 50/60Hz or 100-127V 50/60Hz
Manuals	User, installation and technician’s manuals in English
Temperature range	+2 to +8 °C controlled vaccine zone
Monitoring	Continuous logger/alarm
Product code	SLE/CCE/015
Manufacturer	Jain Scientific Equipments Pvt Ltd (ScienceLab), Ambala, India

What Is the Mains Ref 128L Used For?

The Mains Ref 128L is a store-level refrigerator. It suits a district or sub-district vaccine store, a hospital immunization room or a busy urban health centre that receives bulk deliveries and redistributes them to smaller clinics. With 128 litres of net space it can hold several antigens in separate, labelled sections, which makes stock counts and first-expiry-first-out handling easier.

Since it runs on the grid, match the voltage version to the site: 220-240V or 100-127V, both at 50/60Hz. Place it in a room that stays between +5°C and +43°C, leave clearance around the cabinet for ventilation, and plan how stock will be protected during long power cuts, for example by moving it into pre-cooled cold boxes.

What to Specify When Ordering

- Number of refrigerators and delivery points.
- Voltage version required: 220-240V or 100-127V (50/60Hz).
- Whether 128 litres of net storage fits your stock plan or a larger store model is needed
-

Man