Email : sales@scilabexport.com
Phone: +91-7082934803

Product Name :

Emergency Trolley With Drawers

Product Code :

SLE/HF/14



Email : sales@scilabexport.com
Phone: +91-7082934803

Description :

Emergency Trolley With Drawers (Product Code: SLE/HF/14) is a mobile emergency response cart that pairs a raised-edge work surface with five lockable drawers, so medicines, renewables and small equipment travel together to the bedside. Casualty departments, wards, clinics and nursing skills laboratories use it as the fixed home of their resuscitation stock. It is made by **Jain Scientific Equipments Pvt Ltd (ScienceLab)**, Ambala, as part of its hospital andlaboratory furniture in India.

Specifications

Parameter	Detail
Type	Emergency response trolley with work surface and storage space
Drawers	5 side-to-side drawers on the long edge, for medicine, renewables and small equipment
Drawer heights	Upper 7–10 cm; second 12–15 cm; third 12–15 cm; base 21–27 cm
Drawer fronts	Prefixed holder for content identification strips; recessed finger grip, leaving the front entirely flat
Drawer interior	Customisable with organiser dividers
Locking	One central lock secures all drawers; key unique to each trolley, key-bow folds away from the key-blade to avoid breakage inside the lock
Work surface	Elevated edges (1.2–5 cm high) along one length and both widths, finished with an anti-slip layer
Worktop extension	Flat worktop that slides out from underneath the work surface; 37–40 x 39–40 cm (l x w); ABS or equivalent polymer
Waste and sharps fittings	Integrated fittings with lid for 2 waste baskets (4.5–6 L each, 9–12 L total) and 2 sharps containers (1.0–2.0 L each, 2.0–4.0 L total)
Frame, side panels, base and drawers	Epoxy coated steel plate, ABS or equivalent polymer; 1.5–2.0 mm thickness
Push handle	Push-bar on one short side, austenitic stainless steel 18/10
Castors	Heavy-duty carriage on 4 swivel castors, all 4 with anti-static wheels; 2 with brake, both at the push-bar handle side
Castor construction	Single mold-on wheel, non-hooded for easy maintenance; total-lock brake (wheel and rotational lock); sealed bearings in swivel and wheel; ball-bearing swivel; frame/bracket steel or nylon
Castor wheel size	2.3–3 x 10–12.5 cm (w x diameter)
Protection	Bumpers at all four corners
Overall size	80–86 x 51–60 x 94–105 cm (l x w x h)
Carrying capacity	100–120 kg
Env	

Typi