



Email : sales@scilabexport.com

Phone: +91-7082934803

Product Name :

Handpump SS-Riser 32ND

Product Code :

SLE/PRP/04





Email : sales@scilabexport.com
Phone: +91-7082934803

Description :

Handpump SS-Riser 32ND (Product Code: SLE/PRP/04) is a 3-metre stainless steel riser pipe of 32 mm nominal diameter, paired with one stainless steel connecting rod, used to build the rising main and rod string of a hand pump installed in a borehole or well. Drilling contractors and water-supply programmes order it length by length, because every riser pipe comes with its own 10.8 mm diameter rod. It is supplied by **Jain Scientific Equipments Pvt Ltd (ScienceLab)**, Ambala, India.

Specifications

Parameter	Detail
Riser pipe material	Stainless steel
Nominal diameter	32 mm (1-1/4 inch)
Riser pipe length	3 metres
Pipe ends	Both ends male threaded; one end fitted with a female threaded coupling
Thread protection	HDPE thread protector covering the entire length of the thread on the other end
Connecting rod	One per riser pipe; stainless steel 304 grade
Rod diameter	10.8 mm
Rod ends	M12 rolled male thread at one end; M12 stainless steel female threaded coupling welded at the other end
Rod length	3 metres (+10/-0 mm)
Product code	SLE/PRP/04
Supplied by	Jain Scientific Equipments Pvt Ltd (ScienceLab), Ambala, India

What Is the SS Riser Pipe and Rod Set Used For?

In a lever-type hand pump, the riser pipes form the column that carries water from the cylinder up to the pump head, while the connecting rods inside that column transfer the handle's up-and-down movement to the piston. The Handpump SS-Riser 32ND provides both parts in matching 3-metre lengths, so the installer screws one pipe onto the coupling of the last and joins the rods through their M12 threads as the string is lowered.

Keep the HDPE thread protectors in place until each pipe is about to be joined, because damaged threads are a common cause of leaking joints. Lay pipes and rods on clean supports rather than bare ground during installation, and count the lengths against the planned cylinder depth before the crew goes to site.

What to Specify When Ordering

- Number of riser pipes and connecting rods required for the length of the cylinder
- The nominal diameter of the riser pipe and the diameter of the rod threads
- The length of the riser pipe and the length of the rod

Website: <https://scilabexport.com>, **Email:** sales@scilabexport.com

1226/1-5, Bengali Mohalla, Science Market | 133001, Hariana



Email : sales@scilabexport.com

Phone: +91-7082934803