Email : sales@scilabexport.com
Phone: +91-7082934803

Product Name :

Triple-Beam Balance

Product Code :

SLE/LB/16



Email : sales@scilabexport.com
Phone: +91-7082934803

Description :

The Triple-Beam Balance measures mass up to 2610 g with 0.1 g readability, using three notched, graduated beams and no power supply. A die-cast aluminium body, a 152 mm grade 304 stainless steel pan and magnetic damping suit daily class use, and a 225 g tare takes up the mass of a container.

Triple-Beam Balance specifications

Parameter	Detail
Capacity	2610 g
Readability	0.1 g
Repeatability and linearity	0.2 g each
Tare range	225 g
Calibration	External; zero adjustment
Construction	Die-cast aluminium; metal housing
Pan	152 mm diameter, grade 304 stainless steel
Beams and damping	Notched, tiered and graduated beams with centre reading; magnetic damping
Accessories	Tripod legs for density measurement; weigh-below hook (optional); storage for additional weights; slot for an optional Kensington-type lock
Size and net weight	550 x 110 x 160 mm (W x D x H); 2.7 kg
Minimum order	10 units
Dispatch	Usually within 7 to 10 working days
Supplied by	ScienceLab (Jain Scientific Equipments Pvt Ltd), Ambala, India

Chemistry and physics weighings on the triple-beam balance

Density of a stone by suspension. Stand the balance on its tripod legs, fit the optional weigh-below hook and hang a stone from it on cotton thread. Weigh the stone in air, then again fully under water in a glass beaker that it does not touch. The loss in mass equals the stone's volume in cubic centimetres; divide the mass in air by it for the density.

Conservation of mass. Put a little dilute acid and a small tube of calcium carbonate granules inside a polypropylene conical flask with screw cap and weigh it closed. Tip the flask to mix them, and the reading stays the same. Loosen the cap and the mass falls

Dens
meas