Email : sales@scilabexport.com
Phone: +91-7082934803

Product Name :

Signal Generator & Amplifier

Product Code :

SLE/PHY/292



Email : sales@scilabexport.com
Phone: +91-7082934803

Description :

Signal Generator & Amplifier (Product Code: SLE/PHY/292) is a bench function generator used to produce sine, square, triangular, pulse and TTL/CMOS signals for electronics and physics experiments in schools, colleges and training labs. It covers 1 Hz to 100 kHz in five ranges, andall of its outputs can be used at the same time. It is supplied by **Jain Scientific Equipments Pvt Ltd (ScienceLab)**, Ambala, India, as a function generator for lab use in India and international markets.

Specifications

Parameter	Detail
Waveforms	Sine, square, triangular, pulse and TTL/CMOS-compatible square wave
Frequency range	1 Hz to 100 kHz, adjustable
Range steps	Five steps: 1 Hz, 10 Hz, 100 Hz, 1 kHz and 10 kHz, with a x10 multiplier
Amplitude control	Coarse and fine controls on the front panel
Simultaneous outputs	Pulse, TTL/CMOS and sine/square/triangular outputs all availableat once on the front panel
Pulse and TTL/CMOS level	Fixed amplitude, compatible with TTL/CMOS logic
VCO input	Output frequency follows a DC voltage of 0.1 V to 10 V at the VCO IN socket, with the toggle switch set to external
Mains input	120 V, 60 Hz or 240 V, 50/60 Hz (selectable)
Dimensions	215 x 180 x 130 mm (W x D x H)
Weight	About 1.5 kg
Product code	SLE/PHY/292
Supplied by	Jain Scientific Equipments Pvt Ltd (ScienceLab), Ambala, India

What Is the Signal Generator Used For?

A function generator is the standard signal source for an electronics bench. Students feed its sine output into RC and LC circuits to plot frequency response and find resonance, use the square wave to watch capacitor charging on an oscilloscope, and drive counters, flip-flops and logic gates directly from the TTL/CMOS output. Because the pulse, TTL/CMOS and analogue outputs work simultaneously, one unit can clock a digital circuit while also supplying a test signal.

The VCO input adds a useful extra: a DC voltage between 0.1 V and 10 V sets the output frequency, so students can demonstrate frequency modulation or sweep a filter by hand with a potentiometer. In physics lessons the signal generator for electronics labs doubles as the test sourc er direct ency.

Wha