

## **Product Name :**

Smoothing Unit

## Product Code : SLE/PHY/294

 Smoothing Unit

 + (2)

 Unsmoothed

 DC input

 35V max.

 - (2)

 Maximum output: 35V, BA

 Please observe polarity

## **Description :**

A smoothing unit for reducing ripple from non-regulated power supplies.

The unit comprises a lightweight and efficient toroidal 0.1H inductor with a network of 2,200uF capacitors and diodes.

Maintains a ripple-free output when high currents are drawn.

Up to 8A at 35V, absolute maximum 40V d.c. (d.c. rectified from 28V a.c).

With a supply of 12V at 3A, 1% ripple would be typical.

Will work without suffering damage even at reverse polarity.

Shrouded sockets accept standard 4mm plugs and shrouded plugs.

Technical Specifications : Input Voltage: 0 to 35V, Absolute maximum 40V Current rating: 8A maximum Height including handle is 187mm. Dimensions: 208 x 155 x 115mm (W x H x D).

Contact Science Lab for your Educational School Science Lab Equipments. We are best school science lab equipments suppliers in india, school science lab instruments, school science lab instruments exporter, school science lab instruments manufacturer, school scientific equipments, science educational equipment.

Website: https://scilabexport.com, Email: sales@scilabexport.com

1226/1-5. Bengali Mohalla. Science Market | 133001. Harvana