Email : sales@scilabexport.com
Phone: +91-7082934803

Product Name :

Flexure Testing Machine Manual

Product Code :

SLE/CE/06



Email : sales@scilabexport.com
Phone: +91-7082934803

Description :

Flexure Testing Machine Manual (Product Code: SLE/CE/06) is a motorised mechanical tester used to determine the flexural strength of 40 x 40 x 160 mm mortar prisms by single-point loading in cement and concrete laboratories. Load is applied through a three-roller attachment at 4 to 6 kg/s and read on a proving ring fitted with a sensitive dial gauge, so no electronics are needed to take a reading. It is made by **Jain Scientific Equipments Pvt Ltd (ScienceLab)**, an OEM TVET lab equipment manufacturer, at its own factory in Ambala, India.

Specifications

Parameter	Detail
Capacity	500 kN (as listed; confirm the proving ring range for your specimens)
Type	Motorised, mechanical unit
Specimen	40 x 40 x 160 mm mortar prisms
Loading method	Single-point loading for flexural strength
Rate of loading	Speed adjusted so load increases at 4 to 6 kg/s
Flexure attachment	Supplied; two 10 mm diameter support rollers spaced 100 mm apart, plus a third 10 mm roller equidistant from them that transmits load tothe opposite face of the prism
Load measurement	Proving ring with sensitive dial gauge
Power supply	230 V, single phase, 50 cycles AC
Product code	SLE/CE/06
Manufacturer	Jain Scientific Equipments Pvt Ltd (ScienceLab) — OEM
Country of origin	India (made in Ambala, Haryana)

What Is the Mortar Flexure Testing Machine Used For?

Cement and mortar are graded partly on flexural strength, measured on small prisms. The prism is laid across the two lower rollers, the third roller is brought down onto its centre, and the motor drives the load up at a steady rate until the prism snaps. The operator notes the dial gauge reading at failure and converts it to load for that proving ring, from which flexural strength is worked out.

Because the machine is purely mechanical, it suits polytechnic and university practicals where students should see how load, deflection and strength relate. Keep the rollers clean and free of mortar crumbs, set the loading speed before each series, and handle the proving ring and dial gauge with care, since they carry the measurement.

OEM Manufacturer

This f es as Sc attach a, Harya and